

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A vacuum cleaner, comprising:

a suction head installed at a front end of a suction path ~~that sucks substances by,~~
wherein a vacuum pressure generated by a suction motor, ~~and having~~ draws substances in
through a suction hole ~~on~~ formed in a bottom surface of an outer casing of the suction head
~~through which the substances are sucked~~ and into the suction path;

a brush rotatably installed in the suction hole of the suction head, and ~~rotated~~ configured
to rotatably contact a surface to be cleaned; and

at least one hair tunnel formed ~~on~~ in the suction head ~~such that,~~ wherein an inlet into the
at least one hair tunnel and the brush ~~do not interfere with each other~~ an inlet into the suction
hole are spaced apart from each other on the bottom surface of the outer casing with a
corresponding portion of the bottom surface of the outer casing positioned therebetween such
that the brush installed in the suction hole does not interfere with the at least one hair tunnel,
wherein the at least one hair tunnel ~~preferentially sucks~~ draws thin and long substances from the
surface, ~~and wherein a sweeper is provided at an inlet of the at least one hair tunnel that~~
~~preferentially sucks the thin and long substances from the surface into the at least one hair~~
tunnel.

2. (Currently Amended) The vacuum cleaner of claim 1, wherein the at least one hair tunnel is linked to the front end of the suction path by a first path that is isolated from ~~the a~~ second path that links the suction hole to the front end of the suction path ~~in the suction head~~.

3. (Currently Amended) The vacuum cleaner of claim 2, wherein ~~an the~~ inlet of the at least one hair tunnel surrounds the suction hole, with the corresponding portion of the outer casing of the suction head positioned therebetween.

4. (Currently Amended) The vacuum cleaner of claim 2, wherein ~~an the~~ inlet of the at least one hair tunnel is ~~installed~~ positioned at one of a front portion or a rear portion of the suction hole in a ~~general suction head progress direction~~ corresponding to a movement direction of the suction head.

5. (Canceled).

6. (Currently Amended) The vacuum cleaner of claim ~~1~~ 12, wherein the at least one sweeper comprises a first sweeper that protrudes ~~downwardly~~ downward from ~~a the~~ bottom surface of ~~an end of an the~~ the outer casing along a first peripheral edge of the inlet of the at least one hair tunnel ~~spaced at a predetermined distance from the suction hole~~, and a second sweeper that protrudes ~~downwardly~~ downward from the bottom surface of the end outer casing along a

second peripheral edge of the inlet of the at least one hair tunnel adjacent the suction hole opposite the first peripheral edge, wherein the second peripheral edge is closer to the suction hole than the first peripheral edge is.

7. (Original) The vacuum cleaner of claim 6, wherein the second sweeper is formed in a group bristle shape with a predetermined width.

8. (Original) The vacuum cleaner of claim 6, wherein the first and second sweepers are formed in a comb-tooth shape.

9. (Currently Amended) The vacuum cleaner of claim 8, wherein an interval between ~~the adjacent~~ comb teeth of the second sweeper is ~~smaller less~~ than an interval between ~~the adjacent~~ comb teeth of the first sweeper.

10. (Currently Amended) The vacuum cleaner of claim 9, wherein ~~the~~ comb teeth of the first sweeper are longer than ~~the~~ comb teeth of the second sweeper.

11. (Previously Presented) The vacuum cleaner of claim 10, wherein some of the comb teeth of the first sweeper comprise a support member that reduces an operation resistance by the first sweeper.

Serial No. **10/579,735**

Docket No. **LK-0017**

Amendment dated **March 5, 2010**

Reply to Office Action dated **December 8, 2009**

12. (New) The vacuum cleaner of claim 1, further comprising at least one sweeper provided at the inlet of the at least one hair tunnel, wherein the at least one sweeper extends downward from the bottom surface of the outer casing at a peripheral edge portion of the inlet of the at least one hair tunnel.